



Model FD8-150

Features

- High RPM application is available, specify this requirement when placing order.
- Left side mounted fitting holes and flow control valve are available, specify this requirement when placing order.
- Capable of $\pm .0005$ with short dwell.
- If mounting multiple spindle head to this unit, please choose nose type: FD-8M-150MT4B is recommended.



Spindle Options

(See page 52-53 for drawings and dimensions)

ER40	Pg. 52
FB30	Pg. 52
NT40	Pg. 52
ER50	Pg. 52
MT4A	Pg. 52
MT4B	Pg. 52
MT4B Multi	Pg. 53

Specifications (Unit: metric)

Hydraulic Pressure	280 ~ 490 P.S.I.
Drilling Capacity	1 3/8" (steel)
Stroke	5.5"
Max. Revolution/Minute	1,500RPM
Flow Control Valve	FCC-G03-8
Weight	148 lb
Cylinder Diameter	4.33"
Cylinder Area	Forward 11.0 IN ² , Backward 4.87 IN ²
Thrust Force	3124 lb @ 280 P.S.I.

Consumption Parts

O-Ring for Front Cover	P-90x2, G-115x1, DH-90x1
O-Ring for Piston	P-100x2, G-65x1
O-Ring for Rear Cover	P-55x2, G-105x1
Spindle Bearing	33010x1, 32008x1, 6010Zx1, 6008Zx1
Pulley Bearings	6013Zx1, 51213x1